



40~200mm



250~350mm



DIMENSIONS TABLE

Unit : mm

Nominal Size		DIN PN10				D	D ₁	L	H	H ₁	H ₂	H ₃	A
		d	c	n	h								
40mm	1½"	46	110	4	18	150	86	32	156	75	100	56	220
50	2	57	125	4	18	165	96	35	166	83	110	56	220
65	2½	70	145	4	18	185	116	37	176	93	120	56	220
80	3	78	160	8	18	211	120	37	191	106	135	56	250
100	4	103	180	8	18	238	152	47	206	119	150	56	250
125	5	129	210	8	18	263	190	57	237	132	168	69	320
150	6	150	240	8	22	285	208	62	252	143	183	69	320
200	8	195	295	8	22	340	264	76	283	170	214	69	400
250	10	251	350	12	22	421	332	96	342	211	273	69	400
300	12	303	400	12	22	488	400	116	399	244	330	69	400
350	14	352	460	16	22	539	414	116	426	270	357	69	400

NOTE. The shape and appearance of assembly differ a little with nominal size compared to this drawing.

131	STEM HOLDER (C)	1	PP	Used for Size 250~350mm
9	BOLT (A)	3	STAINLESS STEEL (SUS304)	Used for Size 250~350mm
157	SCREW (F)	4	STAINLESS STEEL (SUS304)	Used for Size 40~200mm
24	CAP (A)	1	PP	
23	SCREW (B)	4	STAINLESS STEEL (SUS304)	
22	LOCKING PLATE	1	PPG	
21	BOLT (B)	1	STAINLESS STEEL (SUS304)	
20	WASHER (A)	1	STAINLESS STEEL (SUS304)	
19	SPRING	1	STAINLESS STEEL (SUS304)	
18	PIN	1	PPG	
17	HANDLE LEVER	1	PPG	
16a	HANDLE INSERTED METAL	1	STAINLESS STEEL (SUS316L)	
16	HANDLE (A)	1	PP	
8	STEM HOLDER (A)	1	PP	Used for Size 40~200mm
6	O-RING (C)	1	□EPDM □FKM □Others ()	
2	DISC	1	PP	
7	STEM	1	□BODY/STEM □PVC/PVC □PP/PP	
1	BODY	1	□PP/PP	
No.	DESCRIPTION	QTY.	MATERIAL	REMARKS

ITEM	ROTARY DAMPER (TYPE57) ASS'Y LEVER TYPE : DIN PN10 40 ^{mm} (1½") ~ 350 ^{mm} (14")			
DRAWN	N.Ito	DATE	SCALE	
CHECKED	Y.Sato	JAN.17.2025		
APPROVED	K.Yoshino	DRAWING No.		
SPECIAL ORDER No.		DP-M1025DE		
ASAHI YUKIZAI CORPORATION				