


DIMENSIONS TABLE



UNIT: mm

NOMINAL SIZE		d	PVC, C-PVC			PP, PVDF				D1	D2	L1 (LIFT)	H	H1	A	A1	A2	S	S1	S2	ACTUATOR TYPE
			d1	l	L	d1	d1'	l	L												
15mm	1/2"	16	20	16	128	19.50	19.3	14.5	125	48	54×66	10	265.7	19.5	110	130	51	25	M5	10	J4M-S6
20	3/4	20	25	19	147	24.50	24.3	16.0	141	60	54×66	10	267.7	17.5	110	130	51	25	M5	10	J4M-S6
25	1	25	32	22	172	31.50	31.3	18.0	164	70	67×80	12	275.2	18.5	110	130	51	25	M5	10	J4M-S6
32	1 1/4	32	40	26	188	39.45	39.2	20.5	177	82	67×80	12	277.5	22.5	110	130	51	25	M5	10	J4M-S6
40	1 1/2	40	50	31	246	49.45	49.2	23.5	231	100	108×108	21	318.5	27.5	110	130	51	45	M6	14	J4M-S10
50	2	52	63	38	294	62.50	62.1	27.5	274	106	123×123	25	332.7	36.0	110	130	51	45	M6	14	J4M-S10



NOTE.

The shape and appearance of assembly differ a little with nominal size compared to this drawing.



22	THRUST RING	1	SUS304(STAINLESS STEEL)	
21	BOLT	4	SUS304(STAINLESS STEEL)	
20	SCREW	2	SUS304(STAINLESS STEEL)	
19	JOINT	1	SUS304(STAINLESS STEEL)	
18	STAND	1	SUS304(STAINLESS STEEL)	
17	BOLT·NUT	4	SUS304(STAINLESS STEEL)	
16	ACTUATOR	1	POLYAMIDE6 etc.	
15	ENSAT	2	SUS303(STAINLESS STEEL)	
14	THRUST RING	1	UHMW-PE	
13	O-RING	1	EPDM	
12	SLEEVE	1	C3604(COPPER ALLOY)	
11	STEM	1	C3604(COPPER ALLOY)	
10	JOINT	1	SUS304(STAINLESS STEEL)	
9	COMPRESSOR	1	PVDF	
8	INSERTED METAL OF DIAPHRAGM	1	SUS304(STAINLESS STEEL)	
7	CUSHION	1	EPDM	Used for PTFE DIAPHRAGM
6	DIAPHRAGM	1	DIAPHRAGM/O-RING □EPDM □PTFE/EPDM □PTFE/FKM □Others	
5	O-RING	2	()	
4	BONNET	1	PPG	
3	UNION NUT	2	□PVC □C-PVC □PP □PVDF	
2	END CONNECTOR	2		
1	BODY	1		
No.	DESCRIPTION	QTY.	MATERIAL	REMARKS

ITEM	TRUE UNION DIAPHRAGM VALVE TYPE 14 ELECTRIC MODEL TYPE J Ass'y		
	Free power supply : AC24~240V		
	DIN : SOCKET END 15mm (1/2") ~50mm (2")		
	OPTION: —		
DRAWN	N. Ito	DATE	SCALE
CHECKED	Y. Sato	Aug. 2, 2024	
APPROVED	K. Yoshino	DRAWING No.	
SPECIAL ORDER No.		T1-AE006DE	
	 ASAHI YUKIZAI CORPORATION		